

ANALOGUE TYRE INFLATORS QUICK GUIDE



TYRE INFLATOR
ANALOGUE
TDR2000



TYRE INFLATOR
DIAL GAUGE
TDR5000



TYRE INFLATOR
DIAL GAUGE
90 PSI



TYRE INFLATOR
DIAL GAUGE



TYRE INFLATOR
DIAL GAUGE



TYRE INFLATOR
DIAL GAUGE



TYRE INFLATOR
DIAL GAUGE



TYRE INFLATOR
LINEAR GAUGE



TYRE INFLATOR
BAR STYLE

SPECIFICATIONS									
Part No.	10.2000	11.0734	11.0634	11.0534 - SPECIAL ORDER	02.0135	02.0140	02.0150	02.4012	02.0100
Operation	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure	Inflate / deflate / measure
Supply pressure max.	200 psi	200 psi	200 psi	200 psi	200 psi	200 psi	200 psi	200 psi	200 psi
Max. inflation	138 psi	174 psi	90 psi	174 psi	145 psi	145 psi	145 psi	120 psi	120 psi
Chuck type	Hold on	Clip on	Clip on	Clip on	Clip on	Hold on	Clip on	Hold on	Hold on
Chuck style	Dual angle	Single straight	Single straight	Single straight	Single straight	Dual angle	Single angle	Dual angle	Dual angle
Scale	psi, kPa	psi, bar	psi, bar	psi, kPa	psi, kPa	psi, kPa	psi, kPa	psi, kPa	psi, kPa
Inlet size	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP	1/4" BSP
Hose length	500 mm	500 mm	500 mm	500 mm	300 mm	320 mm	400 mm	300 mm	300 mm
Accuracy	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi	± 2 psi @ 25 - 75 psi
Inflation volume L/min	500 L/min @ 188 psi	1200 L/min @ 200 psi	1200 L/min @ 200 psi	1200 L/min @ 200 psi	900 L/min @ 145 psi	900 L/min @ 145 psi	900 L/min @ 145 psi	360 L/min @ 180 psi	360 L/min @ 180 psi
IP rating	-	44	-	-	-	-	-	-	-
Advised application	Industrial, workshops	Industrial, workshops	Industrial, workshops	Industrial, workshops	Trade	Industrial, workshops	Industrial, workshops	Workshop, home	Industrial, tractor

