

HOSE REELS
QUICK GUIDE



AIR HOSE REEL	WATER HOSE REEL	AIR HOSE REEL	WATER HOSE REEL	AIR HOSE REEL	AIR HOSE REEL	WATER HOSE REEL	AIR HOSE REEL	AIR HOSE REEL	HOSE REEL
PRO X EXTREME RETRACTABLE	PRO X EXTREME RETRACTABLE	PRO SERIES EXTREME RETRACTABLE	PRO SERIES EXTREME RETRACTABLE	PRO SERIES RETRACTABLE	PRO SERIES RETRACTABLE	PRO SERIES RETRACTABLE	LOCK OFF RETRACTABLE	METAL MANUAL RETRACT	METAL - HEAVY DUTY MULTI PURPOSE

SPECIFICATIONS										
Part No.	58.3012 & 58.3023	58.3034 & 58.3045	58.3067 & 58.2089	58.4012 & 58.4023	58.1056 & 58.1034	58.2012	58.1045	58.0201	58.2567	58.2067
Hose length	20 m & 30 m	20 m & 30 m	8 m & 20 m	8 m & 20 m	15 m & 20 m	32 m	20 m	20 m	40 m	-
Hose I.D	9.2 mm (3/8")	10.5 mm (1/2")	9.2 mm (3/8")	10.5 mm (1/2")	9.5 mm (3/8")	8 mm (5/16")	11.5 mm (1/2")	10 mm (3/8")	8 mm	-
Hose O.D	15.2 mm (5/8")	16.5 mm (5/8")	15.2 mm (5/8")	16.5 mm (5/8")	16 mm (5/8")	12 mm 1/2")	16 mm (5/8")	16 mm (5/8")	12 mm	-
Leader hose length	2 m with 1/4" BSP Male fitting	2 m with brass tap fittings	2 m with 1/4" BSP Male fitting	2 m with brass tap female fitting	2 m with 1/4" BSP Male fitting	2 m with 1/4" BSP Male fitting	2 m with brass tap female fitting	2 m with 1/4" BSP Male fitting	1 m with 1/4" BSP fitting	-
Hose material	Extreme Ultraflex Reinforced Hose	Extreme Ultraflex Reinforced Hose	Extreme Ultraflex Reinforced Hose	Extreme Ultraflex Reinforced Hose	Reinforced PVC braided	Reinforced PU braided	Reinforced PVC braided	Reinforced PVC braided	PU (Polyurethane)	-
Reel/case type	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Retractable/Polypropylene	Manual wind metal open	Manual wind metal open
Auto lock/rewind	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Stop anywhere function	Yes	Yes	-	-	-	-	-	-	-	-
Controlled hose return	Yes	Yes	-	-	-	-	-	-	-	-
Adjustable tension control	Yes	Yes	-	-	-	-	-	-	-	-
Replaceable hose	Yes	Yes	-	-	-	-	-	-	-	-
Max. working pressure	300 psi	150 psi	300 psi	150 psi	300 psi	250 psi	150 psi	250 psi	217 psi	300 psi
Fitting size	1/4" BSP Male	12 mm tap fittings	1/4" BSP Male	12 mm tap fittings	1/4" BSP Male	1/4" BSP Male	12 mm tap fittings	1/4" BSP Male	1/4" BSP Male	Inlet 1/2" BSP swivel with 10 mm (3/8") barbed end Outlet 1/2" BSP Male to 10 mm (3/8") barbed end
Bracket	180° Pivoting	180° Pivoting	180° Pivoting	180° Pivoting	180° Pivoting	180° Pivoting	180° Pivoting	180° Pivoting	360° Swivel base	Pre-drilled holes for wall or trailer mounting
Advised application	Air	Water	Air	Water	Air	Air (long reach)	Water	Air	Air (long reach)	Air / water / electrical leads / chain

